

2.0 Megapixel Day/Night H.264 HD Outdoor Dome Camera

avigilon
THE BEST EVIDENCE™

Avigilon's end-to-end surveillance solutions deliver image detail no other system can match. Avigilon Control Center software, featuring High-Definition Stream Management™ (HDSM™) technology combined with our broad range of megapixel cameras (from 1 MP to 29 MP) provide unprecedented clarity—while effectively managing storage and bandwidth requirements. Our components are scalable and can work together in an end-to-end system, or can be customized to create your own powerful and cost-effective solution.

The innovative H.264 HD dome camera is just one way Avigilon can help provide the very best monitoring and protection.



The 2.0MP H.264 HD outdoor dome camera is a great solution for monitoring both daytime and nighttime outdoor activities. It features an integrated lens for remote focus and zoom control and is ONVIF compliant for no-hassle integration. The 2.0MP dome camera operates on Avigilon's H3 platform, providing this model with improved low light performance and enhanced HDSM features. P-Iris control also allows the camera to automatically set its iris position to maximize image quality in all lighting conditions. This camera is extremely versatile and can work in almost any location, including banks, schools, retail outlets, municipal grounds and buildings, hotels, bars and restaurants.

KEY FEATURES

2.0 megapixel progressive scan CMOS sensor
Unsurpassed image quality
Available with 3-9 mm F1.2 or 9-22 mm F1.6 P-Iris lens with remote focus and zoom
30 images per second at full resolution
69dB true dynamic range
H.264 and Motion JPEG compression
ONVIF compliant API
Multiple video streams
Automatic exposure control and iris control
Automatic removable IR cut filter for IR sensitivity at night
Power over Ethernet, 24 VAC or 12 VDC power input
Audio Input and Output
Analog Video Output
External I/O
Vandal resistant construction and IP66 compliant

Specifications

	2.0-H3-DO1	2.0-H3-DO2
CAMERA	Image Sensor	1/2.7" progressive scan CMOS
	Active Pixels	1920 (H) x 1080 (V)
	Imaging Area	5.9 mm (H) x 3.3 mm (V) (0.231" (H) x 0.129" (V))
	Minimum Illumination	0.2 lux (F1.2) in color mode; 0.02 lux (F1.2) in monochrome mode
	Dynamic Range	69 dB
	Lens	3-9 mm, F1.2, P-Iris, remote focus and zoom
	Angle of View	35° - 98°
	Image Compression Method	H.264 (MPEG-4 Part 10/AVC), Motion JPEG
	Image Rate	30 (all resolutions)
	Streaming	Multi-stream H.264 and Motion JPEG
	Resolution Scaling	Down to 768 x 432
	Motion Detection	Selectable sensitivity and threshold
	Electronic Shutter Control	Automatic, Manual (1/6 to 1/8000 sec)
	Iris Control	Automatic, Manual
	Day/Night Control	Automatic, Manual
	Flicker Control	50 Hz, 60 Hz
	White Balance	Automatic, Manual
	Privacy Zones	Up to 4 zones
	Audio Compression Method	G.711 PCM 8 kHz
	Audio Input	Line input, A/V mini-jack (3.5 mm)
	Audio Output	Line level, A/V mini-jack (3.5 mm)
	Video Output	NTSC/PAL, A/V mini-jack (3.5 mm)
	External I/O Terminals	Alarm In, Alarm Out
NETWORK	Network	100BASE-TX
	Cabling Type	CAT5
	Connector	RJ-45
	API	ONVIF compliant (www.onvif.org)
	Security	Password protection, HTTPS encryption, digest authentication, WS authentication, user access log.
	Protocol	IPv4, HTTP, HTTPS, SOAP, DNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, Zeroconf, ARP
	Streaming Protocols	RTP/UDP, RTP/UDP multicast, RTP/RTSP/TCP, RTP/RTSP/HTTP/TCP, RTP/RTSP/HTTPS/TCP, HTTP
MECHANICAL	Dimensions (ØxH)	152 mm x 109 mm (6.0" x 4.3")
	Weight	1.2 kg (2.6 lbs)
	Dome Bubble	Polycarbonate, clear
	Body	Aluminum
	Housing	Surface mount, vandal resistant
	Finish	Powder coat, cool gray 2
	Adjustment Range	360° pan, 180° tilt, 360° azimuth
ELECTRICAL	Power Source	VDC: 12 V VAC: 24 V PoE: IEEE802.3af Class 3 compliant
	Power Consumption	9 W
	Power Connector	2-pin terminal block
ENVIRONMENTAL	Operating Temperature	-30°C to +50°C (-22°F to 122°F)
	Storage Temperature	-10°C to +70°C (14°F to 158°F)
	Humidity	20 - 80% Relative humidity (non-condensing)
CERTIFICATIONS	Safety	UL 60950 CSA 60950
	Environmental	IK10 Impact Rating
	Electromagnetic Emissions	FCC Part 15 Subpart B Class B
	Electromagnetic Immunity	EN 55024 EN 61000-4-2 EN 61000-4-3
		EN 60950-1 CE Meets IP66 Weather Rating IC ICES-003 Class B EN 55022 Class B EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-11
ORDERING INFORMATION	2.0-H3-DO1	2.0 Megapixel Day/Night H.264 HD 3-9mm Outdoor Dome Camera
	2.0-H3-DO2	2.0 Megapixel Day/Night H.264 HD 9-22mm Outdoor Dome Camera
	H3-DOP-SMOKE	Dome Camera Cover with Smoked Bubble

Outline Dimensions

